

NVR502-16B-P16-IQ / UNV IP Recorder

Equipped with many practical functions and powerful decoding ability. Prime series provides large number of IP camera access and long storage time on more HDDs. Besides, project functions such as LPR, people counting, and fisheye de-warping are supported, and interfaces of alarm I/O, audio I/O, gigabit Ethernet can be supported on all models.



- 16-IP camera, 12MP resolution
- 16 POE ports, up to 30 W/port, up to 240W
- Recording speed up to 320 Mb/s, Packing H.264/H.26
- 1 HDMI, 1 VGA, Gigabit Ethernet interface, 2-SATA
- People counting and versatile analytics features,
- · Remote Access EZView (IOS, Android), EZStation (WI
- Dimensions: 1U, 380 x 318 x 53 mm

Product series

Prime NVR

Technical data

H.264, H.265, Ultra H.265 Support ONVIF (Profile S, Profile G, Profile T) and RTSP protocols Network connection speed, PoE H.264, H.265, Ultra H.265 Height (mm) Length (Depth) (mm) 1 **Gigabit, 16*10/100Mbit PoE Net weight (kg) 1 **Reconstruction Speed Section 1 **Reconstruction 1 **Reconstr		12MP max		HDMI, VGA
T) and RTSP protocols Length (Depth) (mm) 318		H.264, H.265, Ultra H.265	Width (mm)	380
Network and B.F. at C. 19 acts (could be 5		Support ONVIF (Profile S, Profile G, Profile	Height (mm)	53
Network connection speed, PoE 1*Gigabit, 16*10/100Mbit PoE Net weight (kg) 1.8		T) and RTSP protocols	Length (Depth) (mm)	318
i v i i i i i i i i i i i i i i i i i i	Network connection speed, PoE	1*Gigabit, 16*10/100Mbit PoE	Net weight (kg)	1.8