

## AD-800AM / Glass break detector

AD 800-AM is a new generation of acoustic glass break detector with Anti-Mask function which meets the requirements for grade 3 of the new standard EN 50131-2-7-2:2013. The detector is based on the latest microprocessor technology and has a number of advanced algorithms connected to the acoustics of the room (Digital Room Compensation, DRC). Thanks to these algorithms, the detector can distinguish a glass breakage signal from other interferences and boasts high immunity to false alarms. AD 800-AM has a newly developed active Anti-Mask function (overlay protection) with separate relay output for enhanced security. If attempts are made to tamper with the microphone or sensor, an Anti-Mask alarm is triggered.



- New generation acoustic glass break detector
- Equipped with an anti-masking function
- Suitable for standard, tempered and laminated glass
- Compliant with the EN 50131 Grade 3 requirements
- Intended for indoor installation, the device can be mounted either on a ceiling or wall, opposite to the protected glass.
- The detection range spans 165°, which means that one detector can monitor multiple windows in a room

SKU	8003450
GTIN code	5901508451903
Product series	AD

## Technical data

Coverage	9 m, 165 degrees
	Acoustic glass break
	yes
Operating current, normal (mA)	12
Operating temperature	käyttölämpötila: +5 ... +40°C
Width (mm)	68
Length (Depth) (mm)	39
Net weight (kg)	0.124



We withhold the right to make changes

Hedengren Security Oy Ab  
www.hedengren.com  
tel. +358 (0) 207 638 001  
security@hedengren.fi  
PP.KK.VVV