

NBE-4502-AL / IR IP Bullet Camera 2MP

IR IP bullet 1080p AVF H.265 IP67 SMB

- 1/2.8" CMOS Image Sensor, D/N
- minimum illumination color 0.052 lx/m/v 0.008 lx; F1.4, WDR (85dB), digital noise reduction (DNR)
- 1920 x 1080 (2MP Full HD 1080p) 30 - frames/s, H.265/H.264/ MJPEG compression, simultaneous traffic
- 2.8 - 12 mm/ F1.4, DC iris, motor zoom lens, autofocus, infrared LED, 850 nm, lighting distance approx. 60 m
- two-way audio, 1 alarm input and output, Micro SDXC/ Micro SDHC memory card slot, IP66, IK10, working temperature -40°C... +60°C, ONVIF compliant, PoE/24VAC/12VDC
- Motion Detection, Normal Video Analytics (EVA), Analog Output CVBS

Camera type	Bullet camera
Technology	IP
Outdoor installation	Yes
SKU	8004317
Product series	DINION IP 4000i IR



Technical data

Resolution	2	Analog output	Yes
Focal length min	2.8	Ingress protection (IP)	IP67
Focal length max	12	Impact protection (IK)	IK10
Lens type	Motorized zoom	Net weight (kg)	3.1
IR range	60 m		