

NIN-73023-A3AS / IP Dome Camera 2MP HDR

FLEXIDOME IP 7000 VR 1080p 3-9mm IVA SMB

- 1/2.8" CMOS Image Sensor, D/N
- minimum illumination color 0.0075 lx/m/v 0.0011 lx; F1.4, WDR (120dB), digital noise reduction (DNR)
- 1920 x 1080 (2MP Full HD 1080p) 60 - frames/s, H.264/ MJPEG compression, simultaneous traffic
- 10 - 23 mm/F1.3, DC iris, motor zoom lens, autofocus
- two-way audio, 2 alarm inputs and 1 output, Micro SDXC/ Micro SDHC memory card slot, analog output CVBS, IP66, IK10, operating temperature -30°C... +60°C, ONVIF compatible, PoE/12VDC
- Motion Detection, Intelligent Video Analytics (IVA)



Camera type	Dome camera
Technology	IP
Outdoor installation	Yes
SKU	8004334
Product series	FLEXIDOME IP starlight 7000 VR

Technical data

Resolution	2	Analog output	Yes
Focal length min	3	Ingress protection (IP)	IP66
Focal length max	9	Impact protection (IK)	IK10
Lens type	Motorized zoom	Net weight (kg)	0.85
IR range	N/A		