

NIN-70122-F0AS / Fixed Dome Camera 12MP 360°

FLEXIDOME IP panoramic 7000 12MP 360 IVA SMB

- 1/2.3" Progressive Scan CMOS, D/N, 360° panoramic view
- Minimum illumination color 0.55 lx/m/v 0.18 lx; F2.8, WDR (92 dB), digital noise reduction (DNR)
- Fisheye image: resolution 2640 x 2640 (7 MP) - 30 frames/s, Shared image: resolution 1920 x 1080 (2 MP) - 30 frames/s, H.264/ MJPEG compression, simultaneous traffic, image formats: Fisheye, 360° Panorama, EPTZ
- Fixed lens (fisheye) 1.6 mm/F2.8, Integrated microphone, alarm input and output, SDXC/SDHC memory card slot
- motion detection, intelligent video analytics (IVA), IK06, working temperature -20°C... +50°C ONVIF compliant, PoE



Camera type	Fisheye camera
Technology	IP
Outdoor installation	No
SKU	8004335
Product series	FLEXIDOME IP panoramic 7000

Technical data

Resolution	12	Analog output	No
Focal length min	2.1	Ingress protection (IP)	IP00
Focal length max	2.1	Impact protection (IK)	IK06
Lens type	Fixed	Net weight (kg)	0.526
IR range	N/A		