



## A problem has occurred

2026-06-01 23:06:08

### Error message:

This license has expired on 2026-05-30.

### License Information:

License serial no:	3916
Licensee:	Adeona Oy
Product:	PDFReactor Library
Version:	12.0
License Type:	CPU
Amount:	12 Thread(s)
Maintenance Exp. Date:	2026-05-30
Expiration Date:	2026-05-30
Purchase Date:	2015-11-18
Conditions:	[This license is for use on development systems only. It may not be used on staging or productive systems of any kind.]
Sign Date:	2025-06-02 15:11

## N40 / Markeringskilt 40m stamme 1 batt.

N40 er ett henvisningsarmatur i Neptolux N-serien. N-serien er vår nye generasjon armaturer i vårt populære nødlyssystem Neptolux. N-serien utviklet for lave driftskostnader, maksimal energibesparing og med servicefri livslengde i fokus. Long-life komponenter for lavt energiforbruk og lavt CO<sub>2</sub>-avtrykk gjør armaturen til ett miljømessig sterkt valg. Alle produkter i N-serien er helt halogenfrie og levereres med 10 års materialgaranti. Armaturen har 40m leseavstand og symbolskilt. Armaturen kan monteres på vegg eller tak (innfelt som tilvalg). Armaturen ansluttes mot Neptolux nødlyssentral eller Firescape brannalarmsentral for en adressert overvåkning. N20 finnes også i en versjon for anslutning mot UPS eller sentral vekselretter. Armaturen kan også anvendes som en frittstående selvtestende armatur direkte tilkoblet mot 230VAC (via 230V tilkoblingsokkel). Armaturen er konstruert for å fungere selv i lave omgivelsestemperaturer (ned til -25 C) med 1t nøddrift.



- LED long-life dioder, 10 års beregnet livslengde
- Innebygget NiMH batteri, 10 års beregnet livslengde
- Adressert overvåkning uten ekstra kabling
- Montasjefeste med hurtigkobling direkte i tak eller vegg
- IP55 med N-IP-GASKET (bestilles separat)
- IP67 med N40-IP67 (bestilles separat)
- Installasjonsokkel YBN-R/3/WHT (bestilles separat)

ERP nummer	8004989
GTIN kode	06418391000273
Produkt serie	Firescape, Neptolux

## Teknisk data

Leseavstand (m)	40
Batterikapasitet (mAh)	1900
Akkumulator type	NiMH
Driftspenning (VDC)	24-40
IP kapslingsklasse (IP)	IP20
Monteringsmetode	Innfelt montasje
Bredde (mm)	322.22
Høyde (mm)	267.61
Lengde (Dybde) (mm)	0
Nettvekt (kg)	0.283
Farge	Hvit



Vi forbeholder oss retten til å gjøre endringer

Hedengren Security Oy Ab  
[www.hedengren.com/no](http://www.hedengren.com/no)  
 Telefon: 22 27 22 22  
[salg@hedengren.no](mailto:salg@hedengren.no)  
 PP.KK.VVV



REALOBJECTS

PDFReactor®

## Evaluation Version

This PDF document was created by an evaluation version of RealObjects PDFReactor 12.1.0 (17110). The evaluation version is fully functional, but includes this information page. It must not be used for production purposes. The information page and all other evaluation notices must not be removed from the PDF file.

**NOTE:** Conversions in evaluation mode might be slower and the results might have a larger file size than in production mode.

## Buy PDFReactor

To buy a PDFReactor license follow this link:

[Buy PDFReactor online](#)

## About PDFReactor

RealObjects PDFReactor is a powerful formatting processor for converting HTML and XML documents into PDF. It uses Cascading Style Sheets (CSS) to define page layout and styles. The server-side tool enables a great variety of applications in the fields of ERP, eCommerce and Electronic Publishing.

PDFReactor supports HTML5, CSS3 and JavaScript.

It allows you to dynamically generate PDF documents such as invoices, delivery notes and shipping documents on-the-fly. PDFReactor allows you to easily add server-based PDF generation functionality to your application or service. Since PDFReactor runs on a server, the end-user in general does not need any software other than a PDF viewer.

For more information visit [www.pdfreactor.com](http://www.pdfreactor.com)