

N89-O/N / High power escape route luminaire for open spaces

A powerful escape route luminaire well suited for high spaces

- A very powerful escape route luminaire especially for high spaces.
- Round light beam.
- Battery included
- Made of aluminum
- IP55 with separate mounting gasket N-IP-GASKET
- Mounting base: YBN-R/3/WHT



SKU	8006079
GTIN code	06418391000075
ETIM class code	EC001957
Product series	Firescape, Neptolux

Technical data

Lens type	Open area
Battery capacity (mAh)	2900
Battery type	Li-ion
Operating temperature	-25 °C — +40 °C
Operating voltage (VDC)	24 VDC — 40 VDC
Operating voltage (VAC)	24 VAC — 40 VAC
Operating current, normal (mA)	2.5
Operating current, max (mA)	16.5
Ingress protection (IP)	IP21
Impact protection (IK)	N/A
Mounting method	Ceiling mount
Width (mm)	100
Height (mm)	54
Length (Depth) (mm)	100
Net weight (kg)	0.2
Colour	White
Approvals	EN54-18, 0470-CPR-0042



We withhold the right to make changes

Hedengren Security Oy Ab
www.hedengren.com
tel. +358 (0) 207 638 001
security@hedengren.fi
PP.KK.VVV