

IPC324LE-DSF28K-G / UNV IP Dome Camera

The products of the Easy series consist of the EasyBasic and EasyStar series. Their main selling point is to offer excellent performance at an affordable price.

- 4MP, 1/3" progressive CMOS sensor
- Color: 0.003 lux @ (F1.6, AGC ON), 0 lux IR
- Fixed 2.8mm lens, 120dB WDR, IR lights 30 m
- 12 VDC, PoE, IP67, IK10, operating temperature-30 °C to 60 °C

| | |
|----------------------|-------------|
| Camera type | Dome camera |
| Technology | IP |
| Outdoor installation | Yes |
| SKU | 8006194 |
| Product series | Easystar |



Technical data

| | | | |
|------------------|-------|-------------------------|------|
| Resolution | 4 | Ingress protection (IP) | IP67 |
| Focal length min | 2.8 | Impact protection (IK) | IK10 |
| Focal length max | 2.8 | Width (mm) | 109 |
| Lens type | Fixed | Height (mm) | 81 |
| IR range | 30 m | Net weight (kg) | 0.35 |
| Analog output | No | | |

We withhold the right to make changes

Hedengren Security Oy Ab
www.hedengren.com
tel. +358 (0) 207 638 001
security@hedengren.fi
04.12.2024