

N68R-O-3 / Recessed escape route luminaire for open spaces with 3 h battery life

Easy and quickly installable recessed escape route luminaire

- Round light beam
- With a convenient and fast spring mounting.
- No separate mounting frames.
- Also available in black.
- Battery included



| | |
|----------------|---------------------|
| Enclosure | PC/ABS |
| SKU | 8006361 |
| GTIN code | 06418391000631 |
| Product series | FIREscape, Neptolux |

Technical data

| | |
|--------------------------------|---------------|
| Lens type | Open area |
| Battery capacity (mAh) | 6000 |
| Battery type | NiMH |
| Battery type | NiMH |
| Operating temperature | -25°C — +40°C |
| Operating voltage (VDC) | 25 — 40 |
| Operating voltage (VAC) | 25 — 40 |
| Operating current, normal (mA) | 1.3 |
| Operating current, max (mA) | 14.2 |
| Ingress protection (IP) | IP21 |
| Impact protection (IK) | N/A |
| Mounting method | Ceiling mount |
| Width (mm) | 90 |
| Height (mm) | 43 |
| Length (Depth) (mm) | 90 |
| Net weight (kg) | 0.1 |
| Colour | White |



We withhold the right to make changes

Hedengren Security Oy Ab
www.hedengren.com
 tel. +358 (0) 207 638 001
security@hedengren.fi
 PP.KK.VVVV